

**Instruction.** To enlarge page click (+) positive sign third icon from left. Or (+) in the middle and bring the sign into the picture. To search, click on binocular and type in one word or a sentence. To move page, click on hand 2nd row in middle, hold down left mouse button (on pc) and drag. To print page, click on printer icon 2nd from left.

<b>Vacuum cleaner specifications</b>	<b>SL-3</b>	<b>SL-5</b>	<b>SL-6</b>	<b>SL-7</b>
part # for 120 Volt machines	<b>1W12010</b>	<b>1W12020</b>	<b>1W12030</b>	<b>1W12040</b>
Vacuum top material	metal	metal	metal	metal
Vacuum container material	plastic	plastic	plastic	plastic
No. of casters	4	4	4	4
Application	Dry	Dry	Wet-Dry	Wet-Dry
Motor input (Watts)	770	770	770	1340
Recovery capacity <b>gallon</b>	3	5	5	5
Recovery capacity <b>liter</b>	12	20	20	20
Water lift (inches)	85	85	85	105
Airflow (CFM)	93	93	93	108
Cable length (feet)	33	40	40	50
Net weight <b>lb</b>	22	23	26	32
Net weight <b>kg</b>	10	10.5	12	15
Primary dirt collector	paper bag	vacuum tank	vacuum tank	vacuum tank
Pre-filter material	cloth			
Final filtration material	corrugated	cloth	cloth	cloth
Final filtration particle size	5 micron	10 micron	10 micron	10 micron
Efficiency % of final filtration	95%	95%	95%	95%

All vacuum includes 10ft 1-1/2" dia hose

---

---